


DelgadoRecessed Downlight



Features

• Selected LED chip with efficient driver, energysaving with 50000 hours lifespan



Colour Rendering Index ≥80

- Frosted cover with high transmittance
- Excellent heat dissipation design
- Powder coated surface treatment, durable and not easy to fall off







Delgado

TECHNICAL DATA SHEET - DELGADO - 15242 - RECESSED DOWNLIGHT











TECHNICAL DATA

Product Data Recessed Downlight SAMSUNG LED **Lamp Type**

30W Wattage 4000K **Color Temperature** Rated Luminaire Luminous Flux 2,475m **Rated Luminaire Efficiency** 80-85lm/W

IP Rating 44 90° **Beam Angle**

AC220-240V Voltage 50-60 Hz Frequency Range CRI Ra>80 **Power Factor** >0.95 SDCM(Macadam step) < 6 Max Current (mA) 805mA **Output Current** 700mA THD (%) ≤ 15% Safety Class Class II -20°C ~ +40°C **Operating Temperature**

Storage Temperature 25°C

Material Aluminum with Powder coated surface


Finish White + Iron Grey Life Span 60,000 Hours Warranty 6 Years

Applications Residential, Commercial, Hospitality etc.

LED







Cutout: 190mm

TECHNICAL OPTIONS

Wattage	11W/15W/23W
Color Temperature	3000K-6000K
Control	TRIAC/0-10V/DALI

