

## Pito T8 Tube




### Features

- One ended & double ended bypass Type B
- Base: G13 available
- Environmentally friendly without mercury
- 100~120LPW high lumen efficiency
- No mercury glass so NO Regulated Universal Waste rules or fines

 Tube

 IP Rating  
IP20

Colour Rendering Index  
≥85


 Standard Warranty  
5 years warranty

## TECHNICAL DATA SHEET - PITO - 15617 - T8 TUBE WITH MICROWAVE SENSOR



### TECHNICAL DATA

<b>Product Data</b>	T8 Tube
<b>Lamp Base</b>	G13
<b>Lamp Type</b>	EPISTAR LED
<b>Wattage</b>	18W
<b>Color Temperature</b>	6000K
<b>Rated Luminaire Luminous Flux</b>	1890lm
<b>Rated Luminaire Efficiency</b>	105lm/W
<b>IP Rating</b>	20
<b>Beam Angle</b>	120°
<b>Voltage</b>	AC85-265V
<b>CRI</b>	Ra>85
<b>Power Factor</b>	>0.97
<b>Frequency Range</b>	50-60 Hz
<b>Output Current</b>	230mA
<b>Operating Temperature</b>	-20°C ~ +50°C
<b>Safety Class</b>	Class II
<b>Sensor</b>	Microwave Sensor
<b>StandBy Time</b>	2 min
<b>StandBy Brightness</b>	30%
<b>Effective Induction Distance</b>	8-10m
<b>Material</b>	Aluminum + PC
<b>Finish</b>	White
<b>Life Span</b>	50,000 Hours
<b>Warranty</b>	5 Years
<b>Applications</b>	Hospitals, Commercial, Hospitality etc.



### TECHNICAL OPTIONS

<b>Wattage</b>	9W, 20W, 25W
<b>Color Temperature</b>	2700K - 6500K
<b>Switchable</b>	Switchable, DALI, TRIAC, 0-10V