

Tronco T5 Tube



Features

- Solid pins, Wires are fixed on Two stainless steel screws
- PC cover, fire rating V0
- Light transmittance rate 88% for milky cover, 95% for clear cover
- Full pinstripe structure Alum-profile
- Thickness > 1 mm; Coefficient of heat conductivity > 1.5

 **Ceiling**

 **IP Rating**
IP20

Colour Rendering Index
≥85


5 years **Standard Warranty**
warranty

TECHNICAL DATA SHEET - TRONCO 9 - 15697 - T5 TUBE



TECHNICAL DATA

Product Data	T5 Tube
Lamp Base	G5
Lamp Type	EPISTAR LED
Wattage	9W
Color Temperature	4000K
Rated Luminaire Luminous Flux	1170lm
Rated Luminaire Efficiency	130lm/W
Beam Angle	120°
IP Rating	20
Voltage	AC85-265V
CRI	Ra>85
Power Factor	>0.95
Output Current	120mA
Frequency Range	50-60 Hz
SDCM (MacAdam)	<5
Operating Temperature	-20 ~+65°C
UGR	<22
Material	Aluminum + PC
Finish	White
Life Span	50,000 Hours
Warranty	5 Years
Applications	Residential, Hospitals, Commercial, Hospitality etc.



TECHNICAL OPTIONS

Wattage	5W / 7W / 18W / 20W / 25W
Color Temperature	3000K - 6000K
Sensor	PIR, Microwave Sensor
Others	Switchable, DALI, 1-10V, 0-10V, Others