

# Ira Recessed Spotlight



## **Features**

- Best Lumen output efficacy
- Use of high-tech spraying technology, anti-corrosion
- Die cast aluminium body and heat sink designed for effective heat dissipation
- High Light Uniformity
- High value appeareance and durability
- 2.5kV Protection
- 80% Energy Saving



**IP Rating** 

IP44



UGR <19



Standard Warranty



**TRIAC Dimmable** 



### TECHNICAL DATA SHEET - IRA - 18008 - RECESSED SPOTLIGHT











#### **TECHNICAL DATA**

**Product Data** Recessed spotlight **BRIDGELUX LED Lamp Type** 

Driver LIFUD TRIAC Dimming Driver

10W Wattage 3000K **Color Temperature** Rated Luminaire Luminous Flux 950lm **Rated Luminaire Efficiency** 95lm/W **IP Rating** 44 38° **Beam Angle** 


Voltage AC220-240V 50-60 Hz **Frequency Range** CRI Ra>90 >0.9 **Power Factor** 250mA **Output Current Safety Class** Class II **Operating Temperature** -20°C ~ +40°C

SDCM(MacAdam) < 3

Die Cast Aluminum Material


**Finish** White Life Span 60,000 Hours 6 Years Warranty

**Applications** Residential, Commercial, Hospitality etc.









Cutout: 70mm

### **TECHNICAL OPTIONS**

Color Temperature	3000K-6000K
Beam Angle	24°
Control	Switchable/DALI/1-10V/0-10V

