

Ira

Recessed Spotlight




Features

- Best Lumen output efficacy
- Use of high-tech spraying technology, anti-corrosion
- Die cast aluminium body and heat sink designed for effective heat dissipation
- High Light Uniformity
- High value appearance and durability
- 2.5kV Protection
- 80% Energy Saving

 Recessed

 UGR <19

 IP Rating IP44

 6 years Standard Warranty warranty



 TRIAC Dimmable

TECHNICAL DATA SHEET - IRA - 18009 - RECESSED SPOTLIGHT



TECHNICAL DATA

Product Data	Recessed spotlight
Lamp Type	BRIDGELUX LED
Driver	LIFUD TRIAC Dimming Driver
Wattage	10W
Color Temperature	3000K
Rated Luminaire Luminous Flux	950lm
Rated Luminaire Efficiency	95lm/W
IP Rating	44
Beam Angle	38°
Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>90
Power Factor	>0.9
Output Current	250mA
Safety Class	Class II
Operating Temperature	-20°C ~ +40°C
SDCM(MacAdam)	< 3
Material	Die Cast Aluminum
Finish	Black
Life Span	60,000 Hours
Warranty	6 Years
Applications	Residential, Commercial, Hospitality etc.



TECHNICAL OPTIONS

Color Temperature	3000K-6000K
Beam Angle	24°
Control	Switchable/DALI/1-10V/0-10V

