



**Product Specifications:**

Lamp Type: PHILIPS LED  
 Driver: PHILIPS  
 Operating Temp.: -20°C ~ +40°C  
 Material: Die Cast Aluminum  
 Finish: White & Black  
 Lifespan: 60,000 Hours  
 Warranty: 6 Years  
 Applications: Commercial, Retail, Residential, Hospitality

**Product Options:**



Wattage: 5W / 8W  
 CCT: 3000K - 6000K  
 Beam Angle: 15°/24°/30°  
 Control: Switchable / DALI / 1-10V / 0-10V / TRIAC




Genssen X

	SKU	W	CCT	LM	mA	Beam	Size(mm)	Cut(mm)
<b>Genssen</b>	13318	10W	3000K	650lm	250mA	36°	Ø90x100	Ø80
	15391	10W	4000K	700lm	250mA	36°	Ø90x100	Ø80
	13746	10W	6000K	750lm	250mA	36°	Ø90x100	Ø80
<b>Genssen (Black)</b>	(TRIAC) 17198	10W	3000K	650lm	250mA	15°	Ø90x100	Ø80
	(TRIAC) 17200	10W	3000K	650lm	250mA	36°	Ø90x100	Ø80
	(TRIAC) 17199	20W	3000K	1,500lm	500mA	30°	Ø130x110	Ø105
<b>Genssen X</b>	15681	20W	4000K	1,600lm	500mA	30°	Ø120x98	Ø110


AC220-240V IP44 60° CRI>90 PF>0.9



Cutout: Ø80mm



Cutout: Ø105mm



Cutout: Ø110mm

**Product Specifications:**

Lamp Type: PHILIPS LED  
 Driver: PHILIPS  
 Operating Temp.: -20°C ~ +40°C  
 Material: Die Cast Aluminum  
 Finish: White & Black  
 Lifespan: 60,000 Hours  
 Warranty: 6 Years  
 Applications: Commercial, Retail, Residential, Hospitality


**Product Options:**

Wattage: 15W  
 CCT: 3000K - 6000K  
 Beam Angle: 15°/24°/30°  
 Control: Switchable / DALI / 1-10V / 0-10V / TRIAC




	SKU	W	CCT	LM	mA	Beam	Size(mm)	Cut(mm)
<b>Genssen</b>	13321	20W	3000K	1,500lm	500mA	60°	Ø130x110	Ø105
	15392	20W	4000K	1,600lm	500mA	60°	Ø130x110	Ø105
	13747	20W	6000K	1,700lm	500mA	30°	Ø130x110	Ø105
<b>Genssen Square</b>	(TRIAC) 14697	10W	3000K	650lm	250mA	36°	Ø90x100	Ø80x80
	15660	10W	4000K	700lm	250mA	36°	Ø90x100	Ø80x80
	15393	20W	3000K	1,500lm	500mA	36°	Ø130x119	Ø105x105


AC220-240V IP44 30,36°/60° CRI>90 PF>0.9



Cutout: Ø105mm



Cutout: Ø80x80mm



Cutout: Ø105x105mm