

Vic

Recessed Wall/Step Light



Features

- Housing: 12# Die-casting RAL9005 powder coated aluminum T=60-80µm.
- Adhesion of ISO class 1/ASTM class 4B
- Light Window: Glass T=1.8mm
- Gasket: Molding shaped silicone seal
- Recessed Sleeve: PC/ABS ALLOYS



Recessed



IK Rating
IK10



IP Rating
IP65




Standard Warranty

TECHNICAL DATA SHEET - VIC - 18559 - RECESSED WALL/STEP LIGHT



TECHNICAL DATA

Product Data	Wall/Step light
Lamp Type	EDISON LED
Wattage	9W
Color Temperature	3000K
Rated Luminaire Luminous Flux	630lm
Rated Luminaire Efficiency	70lm/W
IP Rating	65
Beam Angle	120°
Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>80
Power Factor	>0.9
Working Temperature	-20°C~ +50°C
Output Current	51mA
Material	Die-casting aluminum
Finish	Dark Grey
Life Span	50,000 Hours
Warranty	5 Years
Applications	Outdoors, Residential, Commercial, Hospitality etc.



Cutout: 303x58mm

TECHNICAL OPTIONS

Color Temperature	4000K-6000K
Finish	Silver Grey, Black
Control	Switchable, TRIAC, 1-10V, Dali, PWM