

# Elda Recessed Wall/Step Light



## **Features**

- Housing: 12# Die-casting aluminum powder coated. T=60-80µm.
- Adhesion of ISO class 1/ASTM class 4B
- Light Window: UVstop & Fireproof PC
- Gasket: Molding shaped silicone seal Recessed Sleeve: PC/ABS ALLOYS











## TECHNICAL DATA SHEET - ELDA - 18560 - RECESSED WALL/STEP LIGHT











#### **TECHNICAL DATA**

**Product Data** Wall/Step light Lamp Type **EDISON LED** 

5W Wattage 3000K **Color Temperature** Rated Luminaire Luminous Flux 350lm **Rated Luminaire Efficiency** 70lm/W 65 **IP Rating** 120° **Beam Angle** 

AC220-240V Voltage Frequency Range 50-60 Hz CRI Ra>80 **Power Factor** >0.5


**Working Temperature** -20°C~ +50°C

**Output Current** 60mA

Material Die Cast Aluminium Body

**Finish** Dark Grey 50,000 Hours Life Span Warranty 5 Years

**Applications** Outdoors, Residential, Commercial, Hospitality etc.





100mm





100mm





Cutout: 88x88mm

85.5mm

### **TECHNICAL OPTIONS**

Color Temperature	4000K-6000K
Finish	Silver Grey, Black
Control	Switchable, TRIAC, 1-10V, Dali, PWM