

## Teo

### Flood/Spike light




### Features

- Housing: CNC 6063# aluminum ,Matt silver/black anodized Finish or powder coated
- Lens: Optical lens , efficiency>85%.
- Glass Cover: Tempered glass. T= 4mm
- Base: Aluminum
- Spike: ABS
- Mounting Type: U bracket&mounting plate for solid ground,spike for soft ground

 Spike

 IP Rating  
IP66

 IK Rating  
IK08



 5 years  
warranty Standard Warranty

## TECHNICAL DATA SHEET - TEO - 19521 - FLOOD/SPIKE LIGHT



### TECHNICAL DATA

<b>Product Data</b>	Spike Light
<b>Lamp Type</b>	CREE LED
<b>Wattage</b>	10W
<b>Color Temperature</b>	3000K
<b>Rated Luminaire Luminous Flux</b>	800lm
<b>Rated Luminaire Efficiency</b>	80lm/W
<b>IP Rating</b>	66
<b>Beam Angle</b>	10°-45° (Adjustable)
<b>Input Voltage</b>	AC110-240V
<b>Output Voltage</b>	3-4V
<b>Frequency Range</b>	50-60 Hz
<b>CRI</b>	Ra>80
<b>Power Factor</b>	0.9
<b>Operating Temperature</b>	-20°C ~ +50°C
<b>Material</b>	6063 Aluminium Body
<b>Diffuser</b>	Tempered Glass
<b>Finish</b>	Matt Black
<b>Lifespan</b>	50,000 Hours
<b>Warranty</b>	5 Years
<b>Applications</b>	Outdoors, Gardens, etc.



### TECHNICAL OPTIONS

<b>Wattage</b>	4W - 15W
<b>Color Temperature</b>	4000K-6000K
<b>Control</b>	Switchable, TRIAC, 1-10V, DALI,0-10V