

Teo

Flood/Spike light



Features

- Housing: CNC 6063# aluminum ,Matt silver/black anodized Finish or powder coated
- Lens: Optical lens , efficiency>85%.
- Glass Cover: Tempered glass. T= 4mm
- Base: Aluminum
- Spike: ABS
- Mounting Type: U bracket&mounting plate for solid ground,spike for soft ground

 Spike



IK Rating
IK08



IP Rating
IP66





Standard Warranty

TECHNICAL DATA SHEET - TEO - 19521 - FLOOD/SPIKE LIGHT



TECHNICAL DATA

| | |
|--------------------------------------|-------------------------|
| Product Data | Spike Light |
| Lamp Type | CREE LED |
| Wattage | 10W |
| Color Temperature | 3000K |
| Rated Luminaire Luminous Flux | 800lm |
| Rated Luminaire Efficiency | 80lm/W |
| IP Rating | 66 |
| Beam Angle | 20°-45° (Adjustable) |
| Input Voltage | AC110-240V |
| Output Voltage | 3-4V |
| Frequency Range | 50-60 Hz |
| CRI | Ra>80 |
| Power Factor | 0.9 |
| Operating Temperature | -20°C ~ +50°C |
| Material | 6063 Aluminium Body |
| Diffuser | Tempered Glass |
| Finish | Matt Black |
| Lifespan | 50,000 Hours |
| Warranty | 5 Years |
| Applications | Outdoors, Gardens, etc. |



TECHNICAL OPTIONS

| | |
|--------------------------|--------------------------------------|
| Wattage | 4W - 15W |
| Color Temperature | 4000K-6000K |
| Control | Switchable, TRIAC, 1-10V, DALI,0-10V |