

## Fresno Neon Flex Strip Light



### Features

- The ultimate lighting solution that combines flexibility, durability, and ease of installation. Made from high quality silicone, this waterproof LED strip is designed to handle any environment.
- With its ability to bend either horizontally or vertically, Fresno Neon Flex allows for easy shaping and contouring, enabling you to create amazing, unique designs.



12M Roll

Colour Rendering Index  
≥90



IP Rating  
IP67

5  
years  
warranty


Standard Warranty

## TECHNICAL DATA SHEET - FRESNO - 19971 - NEON FLEX STRIP LIGHT



### TECHNICAL DATA

<b>Product Data</b>	Strip Light
<b>Lamp Type</b>	Lumileds
<b>LED Qty</b>	120 LEDs/M
<b>Wattage</b>	16W/mtr
<b>Color Temperature</b>	4000K
<b>Rated Luminaire Luminous Flux</b>	1040lm/M
<b>Rated Luminaire Efficiency</b>	65lm/W
<b>IP Rating</b>	67
<b>Beam Angle</b>	120°
<b>Voltage</b>	DC24V
<b>Safety Class</b>	Class II
<b>Frequency Range</b>	50-60 Hz
<b>CRI</b>	Ra>90
<b>Power Factor</b>	>0.9
<b>Operating Temperature</b>	-25°C ~ +50°C
<b>Material</b>	Silicone Body
<b>Life Span</b>	50,000 Hours
<b>Warranty</b>	5 Years
<b>Applications</b>	Outdoors, Residential, Commercial, Hospitality etc.




### TECHNICAL OPTIONS


<b>Wattage</b>	5W, 25W
<b>Color Temperature</b>	3000K, 6000K, RGBW
<b>Control</b>	TRIAC/1-10V/DALI/0-10V

## TECHNICAL DATA SHEET - FRESNO - 19971 - NEON FLEX STRIP LIGHT

### DIMENSIONS




### PHOTOMETRICS




Height	Eavg, Emax	Angle: 114.99deg	Diameter
1m	10.215, 36.65lx		78.475cm
2m	2.5525, 9.165lx		156.775cm
3m	1.135, 4.0725lx		235.4275cm
5m	0.4085, 1.4665lx		392.38cm
7m	0.20845, 0.74825lx		549.3325cm

### OPTIONAL ACCESSORIES



Aluminum Channel



Aluminum Clip



Metal Flexible Channel



Silicone End Cap



Wire



Connector