

Invitar Pro

Street & Area Post-Top Light



Features

- Housing: Die Cast Aluminium with treatment of corrosion protection and UV Proof fluorocarbon powder coating
- Gasket: Made of Thermostable silica gel to improve protection class
- Fastener: Made of stainless steel with high intensity and corrosion protection
- Diffuser: Clear Glass



Installation
Street



IK Rating
IK08




IP Rating
IP65




Standard Warranty

TECHNICAL DATA SHEET - INVITAR PRO - 21376 - STREET & AREA POST-TOP LIGHT



TECHNICAL DATA

Product Data	Area & Post-top Light
Lamp Type	CREE LED
Driver	Meanwell Driver
Wattage	30W
Color Temperature	3000K
Rated Luminaire Luminous Flux	3000lm
Rated Luminaire Efficiency	100lm/W
IP Rating	65
Beam Angle	110°
Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>80
Power Factor	>0.95
Operating temperature	-20°C ~ +50°C
SDCM	<3
Safety Class	Class I
IK Rating	08
Material	Die Cast Aluminium Body
Finish	ESD Dark Grey UV-proof powder coating
Life Span	50,000 Hours
Warranty	5 Years
Applications	Tree-lined roads, Riverside roads, Commercial areas and Parks.



TECHNICAL OPTIONS

Color Temperature	3000K-6500K
Control	Switchable, TRIAC, 1-10V, DALI, 0-10V

TECHNICAL DATA SHEET - INVITAR PRO - 21376 - STREET & AREA POST-TOP LIGHT

DIMENSIONS (UNIT: MM)

