


Delien

Recessed Spotlight (Dual CCT Changeable)



Features

- Best Lumen output efficacy
- Use of high-tech spraying technology, anti-corrosion
- Die cast aluminium body and heat sink designed for effective heat dissipation
- High Light Uniformity
- High value appearance and durability





TECHNICAL DATA SHEET - DELIEN - 21695 - RECESSED SPOTLIGHT



TECHNICAL DATA

Product Data	Recessed spotlight
Lamp Type	CREE LED
Wattage	20W
Color Temperature	3000K/4000K
Rated Luminaire Efficiency	80lm/W
IP Rating	44
Beam Angle	60°
Input Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>90
Power Factor	>0.9
Operating Temperature	-20°C ~ +40°C
SDCM(MacAdam)	< 3
Material	Die Cast Aluminum body
Finish	Grey
Life Span	60,000 Hours
Warranty	6 Years
Applications	Residential, Commercial, Hospitality etc.



110mm



105mm

Cutout: 95mm

TECHNICAL OPTIONS

Wattage	10W / 30W
Beam Angle	15° / 24° / 36°
Control	Switchable/DALI/1-10V/0-10V

TECHNICAL DATA SHEET - DELIEN - 21695 - RECESSED SPOTLIGHT

OPTIONAL ACCESSORIES



SKU 21703
White Fixed Reflector



SKU 21704
Chrome Black Fixed Reflector

OPTIONAL FRAMES



SKU 21699 - Round Single
Dimensions: 105x34mm
Cutout: 95mm



SKU 21700 - Round Double
Dimensions: 239x125x47mm
Cutout: 223 x 112mm



SKU 21697 - Round Trimless
Dimensions: 115x34mm
Cutout: 95mm



SKU 21698 - Round Double Trimless
Dimensions: 222x108x47mm
Cutout: 224 x 111mm

OPTIONAL LENS



SKU 21702
36° lens