



Freja

Street & Area Post-Top Light



 **Installation**
Street

 **IK Rating**
IK08

 **IP Rating**
IP65


5 years
warranty **Standard Warranty**

TECHNICAL DATA SHEET - FREJA - 21644 - STREET & AREA & POST-TOP LIGHT



TECHNICAL DATA

Product Data	Post-top Light
Lamp Type	LUMILEDS
Driver	Meanwell
Wattage	40W
Color Temperature	3000K
Rated Luminaire Luminous Flux	4000lm
Rated Luminaire Efficiency	100lm/W
IP Rating	65
Beam Angle	360°
Input Voltage	AC220-240V
Output Voltage	DC30V
Frequency Range	50-60 Hz
CRI	Ra>80
Power Factor	0.9
THD	<15%
SDCM	<3
Safety Class	Class I
Operating Temperature	-20°C ~ +50°C
Dimensions	φ200mm x 3meters
Material	Aluminum ESD UV-proof powder coating
Diffuser	PMMA Diffuser
Finish	Black
Lifespan	50,000 Hours
Warranty	5 Years
Applications	Outdoors, Gardens, Parks, etc.



TECHNICAL OPTIONS

Wattage	30W/50W/60W
Color Temperature	2700K-6500K
Finish	Grey / Customisable
Control	Switchable, TRIAC, 1-10V, DALI,0-10V

TECHNICAL DATA SHEET - FREJA - 21644 - STREET & AREA & POST-TOP LIGHT

DIMENSION (UNIT:MM)

