

Invitar Pro

Bollard & Pathway light



Features

- Finishing: Aluminum with treatment of high corrosion resistance and UV-proof powder coating
- Fastner: 304 stainless steel



Bollard



IP Rating
IP65



IK Rating
IK08





Standard Warranty

TECHNICAL DATA SHEET - INVITAR PRO - 21375 - BOLLARD & PATHWAY LIGHT



TECHNICAL DATA

Product Data	Area & Post-top Light
Lamp Type	CREE LED
Driver	Meanwell Driver
Wattage	20W
Color Temperature	3000K
Rated Luminaire Luminous Flux	2000lm
Rated Luminaire Efficiency	100lm/W
IP Rating	65
Beam Angle	100°
Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>80
Power Factor	>0.95
Operating temperature	-20°C ~ +50°C
SDCM	<3
Safety Class	Class I
IK Rating	08
Material	Die Cast Aluminium Body
Finish	ESD Dark Grey UV-proof powder coating
Life Span	50,000 Hours
Warranty	5 Years
Applications	Tree-lined roads, Riverside roads, Commercial areas and Parks.



TECHNICAL OPTIONS

Color Temperature	3000K-6000K
Control	Switchable, TRIAC, 1-10V, Dali

TECHNICAL DATA SHEET - INVITAR PRO - 21375 - BOLLARD & PATHWAY LIGHT

DIMENSIONS (UNIT: MM)

