Ewo

Flood light
(Wattage & CCT Changeable)



Features

- PET reflector for high lumen efficacy of 140lm/w
- Comfortable lighting effect and effectively glare control by adopting newly designed frosted diffuser
- Optional to equip with infrared sensor for intelligent power saving
- Equipped with 6KV SPD for better protection under extreme power condition

Flood

IK Rating
IK08

IP Rating
IP66

5 years warranty **Standard Warranty**

SYV Iluminacion Europea, Sociedad Limitada
Avda San Pablo 28 - 28820,
Cosloda (Madrid) Spain

© 2025 SYV


Ewo

TECHNICAL DATA SHEET - EWO - 20745 - FLOOD LIGHT





TECHNICAL DATA

Product Data	Flood Light
Lamp Type	LUMILED's
Wattage	150W/180W/200W
Color Temperature	3000K/4000K/6500K
Rated Luminaire Efficiency	140lm/W
IP Rating	66
Beam Angle	120°
Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>70
Power Factor	>0.95
SDCM	<3
IK Rating	08
Operating Temperature	-45 °C to +45 °C
Surge	6KV
Safety Class	Class I
Material	Die cast aluminium body
Lens	Frosted Glass
Finish	Black
Life Span	50,000 Hours
Warranty	5 Years
Applications	Outdoors, Commercial, Hospitality etc.









TECHNICAL OPTIONS

Wattage	80W/100W/150W
CCT	3000K - 6000K
Control	Switchable, TRIAC, 1-10V, DALI
Installation	U bracket Mount, Trunion, Slip Fitter, Knuckle

SYV Iluminacion Europea, Sociedad Limitada
Avda San Pablo 28 - Naves 15 y 2 - 28820
Cosloda (Madrid) Spain
SYV Design is constantly developing and improving it's products. The right is reserved to change specification without prior notification or public announcement.