


# **Timón**Suspended Mounted



# **Features**

- High brightness, adopting high quality
- Enery saving up to 85%, high efficiency power supply, low powerconsumption
- Thin & light design achieves high performance and low cost





Colour Rendering Index ≥80





# TECHNICAL DATA SHEET - TIMÓN - 15633 - SUSPENDED MOUNTED











### **TECHNICAL DATA**

**Product Data** Suspended Mounted

**Lamp Type** OSRAM LED Driver **OSRAM** Wattage 60W 4000K **Color Temperature** Rated Luminaire Luminous Flux 3600lm **Rated Luminaire Efficiency** 60lm/W **IP Rating** 42 **Beam Angle** 160°

AC220-240V Voltage **Frequency Range** 50-60 Hz CRI Ra>80 **Power Factor** >0.9

-20°C ~ +40°C Operating temperature

**SDCM** <6

Dimension Ø800x13x30mm

Aluminum Body+PMMA Diffuser Material

**Finish** White Life Span 50,000 Hours 5 Years Warranty

Residential, Hospitality, Commercial, etc. **Applications** 









D: 800mm

## **TECHNICAL OPTIONS**

Wattage	80W/140W
Color Temperature	3000K-6500K
Control	TRIAC, 1-10V, DALI