

Nuevo Flood light



Features

• PET reflector for high lumen efficacy of 135lm/w

 Comfortable lighting effect and effectively glare control by adopting newly designed frosted diffuser

Optional to equip with infrared sensor for intelligent power saving

• Equipped with 10KV SPD for better protection under extreme power condition

Surface

IP Rating

 $\mathbf{5}_{\mathbf{x}}^{\mathbf{w}} \overset{\text{Standard Warranty}}{\mathbf{x}}$



TECHNICAL DATA SHEET - NUEVO - 15694 - FLOOD LIGHT













TECHNICAL DATA

Product Data Flood Light **Lamp Type** LUMILED's Driver **PHILIPS Driver**

150W Wattage 5000K **Color Temperature** Rated Luminaire Luminous Flux 20,250lm **Rated Luminaire Efficiency** 135lm/W **IP Rating** 66 S14: 60° AC220-240V

Beam Angle Voltage 50-60 Hz **Frequency Range** CRI Ra>70 >0.95 **Power Factor SDCM** <5 THD (%) ≤10% **IK Rating** 80


Operating Temperature -30 °C to +50 °C

4KV Surge Class I Safety Class


Material Die cast aluminium body Polycarbonate, Tempered glass Lens

Aluminium Grey Finish Life Span 50,000 Hours Warranty 5 Years

Applications Outdoors, Commercial, Hospitality etc.



LED



TECHNICAL OPTIONS

Wattage 100W/200W/250W/300W **Color Temperature** 4000K Control 1-10V dimming control; DALI