

# **Ostra Ceiling light**



## **Features**

• Ostra adopts high lumen SMD2835 LED, high light Surface transmission polycarbonate diffuser with even light output



• It is competitive in quality and price with energy saving more than 75%-90%

• High efficiency and low energy consumption.

**IP Rating** IP54

**Colour Rendering Index** ≥80

**Standard Warranty** 



## TECHNICAL DATA SHEET - OSTRA - 16763 - CEILING LIGHT











#### **TECHNICAL DATA**

**Product Data** Ceiling light

PHILIPS SMD 2835 LED **Lamp Type** 

Driver LIFUD DRIVER

10W Wattage 6000K **Color Temperature** Rated Luminaire Luminous Flux 860lm **Rated Luminaire Efficiency** 86lm/W **IP Rating** 54 120° **Beam Angle** Voltage 230V AC 50-60 Hz **Frequency Range** CRI Ra>80 >0.5 **Power Factor** 

**Operating Temperature** -20°C ~ +40°C Material Polycarbonate Body


**Finish** White

Life Span 50,000 Hours

Warranty 5 Years

**Applications** Residential, Commercial, Hospitality etc.

Α+









230mm

### **TECHNICAL OPTIONS**

**Energy Efficiency Class** 

18W / 24W Wattage **Color Temperature** 2700K - 6500K

Switchable, 0-10V, 1-10V, TRIAC, DALI Control